



Centrisart® G-16

All Purpose Centrifuge

Advantages

- High capacity
- Flexible range of applications
- Suitable for all laboratory applications
- Volume | capacity: 4 × 400 ml | 1,600 ml



Product Description

The Centrisart® G-16 benchtop centrifuge was specifically developed for high-capacity applications. This centrifuge also has the option of high speed of 15,300 rpm which allows it to be also used for molecular biology applications. The low profile and damping system lets the centrifuge fit on every laboratory benchtop and ensures operation to be quite, simple and comfortable. Centrisart® G-16 comes with different rotor options to accommodate almost all vessel types, which can be used for low to high throughput. The centrifuge is also available in a refrigerated model, the Centrisart® G-16C.

The ergonomic design, low profile and extremely quiet noise level makes it easy to set up the centrifuge, simplifies sample loading and unloading as well as allows extremely quiet noise level.

This high-capacity centrifuge can be used for nearly every application. With the use of adapters, the Centrisart® G-16 is perfectly appropriate for small volumes such as PCR or molecular biology and larger volumes such as phase separation of solutions.

When working with samples that cannot be churned up, a gradual deceleration curves ensures gentle deceleration and prevents sample from mixing. This function is also beneficial when working with microtiter plates.

The Centrisart® G-16 is an extremely high quality product and meets the highest safety standards. It comes with a secure lid that electronically locks and rotor cover caps that protect against aerosol emissions. The centrifuge also has an automatic rotor detection which prevents mix-ups and an imbalance control sensor which prevents it from starting samples exhibiting deviating weights.

Technical Specifications

Max. speed rpm	15,300
Max. capacity	4 × 400 ml
Max. gravitational field	21,460 g
Min. speed rpm	200
Display	Concise display, backlit keys
Control panel	Easy, 1-button intuitive operation
Motor	Maintenance-free, brushless drive motor
Lid-lock release	Electromechanical locked lid, automatic lid-lock release
Lid	Inspection window for independent speed measurement, easy-to-open lid port
Rotor	Rotor detection for fixed angle rotors, swinging rotors
Rotor chamber	Stainless-steel
Imbalance safety mechanism	Automated imbalance control
Programs	50
Acceleration curves	10
Deceleration curves	10
Rotor safety	Automatic detection, cycle counting of the rotors
Dimensions (W × D × H)	460 × 600 × 355 mm
Height with open lid	785 mm
Weight	48 kg
Noise level at max. speed	<57 dB

Electrical connection data

Power consumption	500 W
G-16-1EU	220–240 V; 50 60 Hz
G-16-1US	110–120 V; 60 Hz
G-16-1JP	100 V; 50 60 Hz

Accessories

Order number	Description
YCSR-A5B	Angle rotor 6 × 50 ml, for vessels made of plastic or stainless-steel Ø 28.5 × 101.5 mm, with hermetically sealed aluminum lid
YCSR-A6B	Angle rotor for 24 × 1.5–2 ml reaction vials, with hermetically sealed aluminum lid
YCSR-A7B	Angle rotor 4 × 80/85 ml, for vessels made of plastic or stainless-steel Ø 38 × 103 mm, with hermetically sealed aluminum lid
YCSR-A8B	Angle rotor 6 × 85 ml for vessels made of plastic or stainless-steel Ø 38 × 112 mm, with hermetically sealed aluminum lid
YCSR-S2B	Swinging rotor, 4 inserts, for buckets B8Bdia85mmS2B
YCSR-S6B	Complete set – swinging rotor including carriers for microtiter plates and caps. Max. height 55 mm; max. load per carrier 290 g
YCSB-B8B	Round bucket, sealable with cap, for round carriers d 85 mm, A2Bxxxx to A8Bxxxx, and 400 ml bottle, max. vessel length approx. 110 mm, 1 set = 2 pcs.
YCSA-C3B	Round carrier for five 15-ml culture tubes, max. Ø 23 mm, 1 set = 2 pcs.
YCSA-C4B	Round carrier for three 50-ml culture tubes, 1 set = 2 pcs.
YCSA-C5B	Round carrier for 1 flat-bottom bottle (approx. 250 ml), max. Ø 61,5 × 90–125 mm, 1 set = 2 pcs.
YCSA-C6B	Round carrier for twenty 1.5 2.0 ml reaction vials, max. Ø 11 mm, 1 set = 2 pcs.
YCSA-C7B	Round carrier for nine 15-ml culture tubes, caps, max. Ø 23 mm, 1 set = 2 pcs.
YCSA-C8B	Round carrier for four 50-ml culture tubes (without caps), 1 set = 2 pcs.
YCSM-B8B	Round locking cap for buckets B8Bdia85mmS2B
YCST-G16	Centrifuge table made of painted steel housing with 2 doors and room for accessories, moveable, with locking castors W 650, D 647, H 497 mm for G16

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany

Sartorius Lab Instruments
GmbH & Co. KG
Weender Landstrasse 94-108
37075 Goettingen

Phone +49.551.308.0
Fax +49.551.308.3289

France & Suisse Romande

Sartorius France
2, rue Antoine Laurent de Lavoisier
ZA de la Gaudrée
91410 Dourdan

Phone +33.1.70.62.50.00
Fax +33.1.64.59.76.39

Austria

Sartorius Austria GmbH
Modecenterstrasse 22
1030 Vienna

Phone +43.1.7965760.0
Fax +43.1.7965760.24

Belgium

Sartorius Belgium N.V.
Rue Colonel Bourg 105
1030 Bruxelles

Phone +32.2.756.06.90
Fax +32.2.481.84.11

Finland & Baltics

Sartorius Biohit Liquid Handling Oy
Laippatie 1
00880 Helsinki

Phone +358.9.755.951
Fax +358.9.755.95.200

Hungary

Sartorius Hungária Kft.
Kagyló u. 5.
2092 Budakeszi

Phone +3623.457.227
Fax +3623.457.147

Ireland

Sartorius Ireland Ltd.
Unit 41, The Business Centre
Stadium Business Park
Ballycoolin Road
Dublin 11

Phone +353.1.8089050
Fax +353.1.8089388

Italy

Sartorius Italy S.r.l.
Viale A. Casati, 4
20835 Muggiò (MB)

Phone +39.039.4659.1
Fax +39.039.4659.88

Netherlands

Sartorius Netherlands B.V.

Phone +31.30.60.53.001
Fax +31.30.60.52.917

info.netherlands@sartorius.com

Poland

Sartorius Poland sp.z o.o.
ul. Wrzesinska 70
62-025 Kostrzyn

Phone +48.61.6473830
Fax +48.61.6473839

Russian Federation

LLC "Sartorius ICR" and LLC "Biohit"
Uralskaya str. 4, Lit. B
199155, Saint-Petersburg

Phone +7.812.327.5.327
Fax +7.812.327.5.323

Spain & Portugal

Sartorius Spain, S.A.
Avda. de la Industria, 32
Edificio PAYMA
28108 Alcobendas (Madrid)

Phone Spain +34.902.123.367
Phone Portugal +351.800.855.800
Fax Spain +34.91.358.96.23
Fax Portugal +351.800.855.799

Switzerland

Sartorius Mechatronics Switzerland AG
Ringstrasse 24a
8317 Tagelswangen (ZH)

Phone +41.44.746.50.00
Fax +41.44.746.50.50

U.K.

Sartorius UK Ltd.
Longmead Business Centre
Blenheim Road, Epsom
Surrey KT19 9QQ

Phone +44.1372.737159
Fax +44.1372.726171

Ukraine

LLC "Biohit"
Post Box 440 "B"
01001 Kiev, Ukraine

Phone +380.44.411.4918
Fax +380.50.623.3162

Americas

USA

Sartorius Corporation
5 Orville Drive, Suite 200
Bohemia, NY 11716

Phone +1.631.254.4249
Toll-free +1.800.635.2906
Fax +1.631.254.4253

Argentina

Sartorius Argentina S.A.
Int. A. Avalos 4251
B1605ECS Munro
Buenos Aires

Phone +54.11.4721.0505
Fax +54.11.4762.2333

Brazil

Sartorius do Brasil Ltda
Avenida Senador Vergueiro 2962
São Bernardo do Campo
CEP 09600-000 - SP- Brasil

Phone +55.11.4362.8900
Fax +55.11.4362.8901

Canada

Sartorius Canada Inc.
2179 Dunwin Drive #4
Mississauga, ON L5L 1X2

Phone +1.905.569.7977
Toll-Free +1.800.668.4234
Fax +1.905.569.7021

Mexico

Sartorius de México S.A. de C.V.
Circuito Circunvalación Poniente
No. 149
Ciudad Satélite
53100, Estado de México
México

Phone +52.5555.62.1102
Fax +52.5555.62.2942

Asia | Pacific

Australia

Sartorius Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175

Phone +61.3.8762.1800
Fax +61.3.8762.1828

China

Sartorius Scientific
Instruments (Beijing) Co., Ltd.
33 Yu An Road, Airport Industrial Park
Zone B,
Shunyi District, Beijing 101300,
P.R.China

Phone +86.10.8042.6300
Fax +86.10.8042.6486

Hong Kong

Sartorius Hong Kong Ltd.
Unit 1012, Lu Plaza
2 Wing Yip Street
Kwun Tong
Kowloon, Hong Kong

Phone +852.2774.2678
Fax +852.2766.3526

India

Sartorius Weighing India Pvt. Ltd.
#69/2-69/3, NH 48, Jakkasandra,
Nelamangala Tq
562 123 Bangalore, India

Phone +91.80.4350.5250
Fax +91.80.4350.5253

Japan

Sartorius Japan K.K.
4th Fl., Daiwa Shinagawa North Bldg.
8-11, Kita-Shinagawa 1-chome
Shinagawa-ku, Tokyo, 140-0001 Japan

Phone +81.3.3740.5408
Fax +81.3.3740.5406

Malaysia

Sartorius Malaysia Sdn. Bhd
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur, Malaysia

Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore

Sartorius Singapore Pte. Ltd
1 Science Park Road,
The Capricorn, #05-08A,
Singapore Science Park II
Singapore 117528

Phone +65.6872.3966
Fax +65.6778.2494

South Korea

Sartorius Korea Ltd.
8th Floor, Solid Space B/D,
PanGyoYeok-Ro 220, Bundang-Gu
SeongNam-Si, GyeongGi-Do, 463-400

Phone +82.31.622.5700
Fax +82.31.622.5799

Thailand

Sartorius (Thailand) Co. Ltd.
129 Rama 9 Road,
Huaykwang
Bangkok 10310

Phone +66.2643.8361-6
Fax +66.2643.8367



◀ www.sartorius.com